

Technische gegevensoverzicht

Type	Ø (mm)	Breedte (mm)	Druk PN	Druk WD
 UNI-Grip	21-172	45-110	16	32 tot 70
	188-745	138-146	2.5 tot 16	6 tot 25
 UNI-Plastgrip	39-172	60-110	10	16
	175-640	140-146	2.5 tot 10	6 tot 16
 UNI-Combigrp	39-172	60-110	10	16
	175-640	140-146	2.5 tot 10	6 tot 16
 UNI-Flex	21-172	45-110	16	25
	188-2090 Groter op aanvraag	140-206 280-420	2.5 tot 16	6 tot 25
 UNI-Rep	36-172	60-110	16	25
	188-745 Groter op aanvraag	140-206 280-420	6 tot 16	10 tot 25

	Ø (mm)	Aantal klemmen	Kwaliteit van het materiaal	dikte van het materiaal
UNI-Coupling	21-47.5 47.5-172	7 15	standaard W5	tot 5 mm dikte

Aansluiting	Metaal - Metaal	Plastic - Plastic	Metaal - Plastic	Stijf / Flexibel
UNI-Grip	X			stijf
UNI-Plastgrip		X		stijf
UNI-Combigrp			X	stijf
UNI-Flex	X	X	X	flexibel
UNI-Rep	X	X	X	flexibel

Afdichtingsmateriaal	EPDM > 21-172 mm	EPDM > 172 mm	NBR	Viton
Temperatuurbereik	-30 °C - +125 °C	-30 °C - +80 °C	-20 °C - +80 °C	-20 °C - +180 °C
Medium	drinkwater, afvalwater, perslucht, alcohol en vaste stoffen	drinkwater, afvalwater, perslucht, alcohol en vaste stoffen	water, gas, olie, brandstof en andere koolwaterstoffen	Ozon, zuurstof, zuren, gas, olie en brandstof (alleen met veranker- inzetstukken

Kwaliteit	Behuizing	Vergrendelplaten	Bouten	Verankering
W5	1.4571 / 316 Ti	1.4571 / 316 Ti	A4 - 80 / 316 Ti	1.4404 / 316 L & 1.4310 / 301